



RoHS Compliant




SPECIFICATION:

- Voltage rating:
  AC, DC, 30V(50HZ)
- Current rating:
  0.2A, DC(AWG#36)
  0.5A, DC(AWG#32)
- Withstand voltage:
  200V AC/minutes
- Working Temperature:
  -25°C~ +85°C
- Insulation resistance:
  >=500MΩ
- Contact resistance:
  <=0.02Ω
- Terminal mtr'l:
  Phosphor Bronze Tin Plated
- Material:
  Housing-PA9T,UL94V-0

Pin No.	DIM.A	DIM.B	DIM.C	DIM.D	DIM.E
2	3.80	0.80	3.00	2.40	2.00
3	4.60	1.60	3.80	3.20	2.80
4	5.40	2.40	4.60	4.00	3.60
5	6.20	3.20	5.40	4.80	4.40
6	7.00	4.00	6.20	5.60	5.20
7	7.80	4.80	7.00	6.40	6.00
8	8.60	5.60	7.80	7.20	6.80
9	9.40	6.40	8.60	8.00	7.60
10	10.20	7.20	9.40	8.80	8.40
11	11.00	8.00	10.20	9.60	9.20
12	11.80	8.80	11.00	10.40	10.00
13	12.60	9.60	11.80	11.20	10.80
14	13.40	10.40	12.60	12.00	11.60
15	14.20	11.20	13.40	12.80	12.40
16	15.00	12.00	14.20	13.60	13.20
17	15.80	12.80	15.00	14.40	14.00
18	16.60	13.60	15.80	15.20	14.80
19	17.40	14.40	16.60	16.00	15.60
20	18.20	15.20	17.40	16.80	16.40
21	19.00	16.00	18.20	17.60	17.20
22	19.80	16.80	19.00	18.40	18.00
23	20.60	17.60	19.80	19.20	18.80
24	21.40	18.40	20.60	20.00	19.60
25	22.20	19.20	21.40	20.80	20.40
26	23.00	20.00	22.20	21.60	21.20
27	23.80	20.80	23.00	22.40	22.00
28	24.60	21.60	23.80	23.20	22.80
29	25.40	22.40	24.60	24.00	23.60
30	26.20	23.20	25.40	24.80	24.40

Ordering Information

WB	3	XX	PT	A	R-44
0.8Ph Wafer	Solder/PCB 3:SMT RA	02~30Pin	Contact Plated PT:Tin		Packaging R:Reel



RECOMMENDED PCB LAYOUT

REV.	REVISION RECORD	DATE
A	Original	04/17/24"

General Tolerance
LINEAR 0.0 ±0.30, 0.00 ±0.25 ANGLE ±3°

UNIT: mm

A4	NAME
APPROVED	WENNY
DESIGNER	GRACE
DRAWN	JINDAR

ARIBA TECHNOLOGY CO., LTD.

TITLE: 0.8Ph Wafer SMT Right Angle 1.85H

DWG.NO: WB3XXPTAR-44 REV. A

SCALE 1 : 1 SHEET 1 OF 1